



21951 – Cty Rd DD New Auburn WI. 54757

Office 715-237-2678

Email: bjorkstrandroofing@yahoo.com

*“The Last Roof You Will EVER Need
In Your Lifetime”*

www.Wimetalroofing.com

Common Questions asked about our Heating Mats

- Our Heaters are a wire wound built resistant heater sandwiched in Silicone
 - Typically our heaters are 10” wide with a melt band of 14”. We stock 10ft, 8ft, 6ft, 4ft, and, 3ft lengths.
 - The above Heaters are 240V, although we do stock 120V Heaters.
 - The Heaters have a 3M adhesive backing which enable them to adhere to most roof underlayment.
 - The Heaters work under asphalt shingles, all metal, and synthetic shake and slate products.
 - They do not transfer heat efficiently under clay tiles or cedar shakes. For these applications we advise a horizontal metal band, in which our heaters are placed under.
 - We have the only logical heaters for Flat Roof applications.
 - We offer a 100% defrost of the roof edge, or valley area.
 - Our system is regulated via a simple timer, or a moisture/temperature Sensor
 - The Heaters conform to all Building Code requirements.
 - The Heaters have a UL designation on them and are designed specifically for snow melt applications. A 20 amp dedicated circuit connected to a GFE circuit breaker is required by code.
 - An electrical contractor is required to make final connections.
- COMPETITION
- Besides the use of unsightly heat tape looped on the edge of the roof, our competition is limited.